



RPR750 Radio Paging Receiver

Time critical messaging

Designed for professionals who demand robust and resilient communications, the RPR750 pager delivers the highest standards of performance to the workplace.

Supporting a range of features, the RPR750 ensures that time critical messages are seen, read and heard whatever the conditions.

Stored speech and full message retrieval

To ensure fast, effective response, the RPR750 supports stored speech and text. This enables voice and text messages to be retrieved and replayed at the touch of a button. The RPR750 is capable of recording up to 5 messages with an overall maximum recording capacity of 2 minutes.

Speech and alert tone volume control

With the volume control feature you can determine the desired level of alert or speech volume. For hands-free operation, set volume to maximum, for minimal disturbance set to minimum.

Bright crystal-clear display

With its bright, crystal-clear, 14-character display, the RPR750 is exceptionally easy to read. Incorporating a powerful luminescent backlight, the RPR750 can be seen in all lighting conditions from bright sunlight to total darkness.

Multiple addresses

The RPR750 Mk7 variant supports up to ten receiver addresses or CAP codes. This feature ensures that a single user, or a team of 5,000 members, can be alerted instantly with a tone, text or speech message.

Key features

- Stored voice, with up to 2 minutes of recordable speech
- One-way speech
- Bright crystal-clear display
- Multiple tone alerts plus volume escalation
- Available in UHF, VHF and HF
- Tough, dust and water-resistant IP54 case with grip-tight clip
- Full alphanumeric text
- Intrinsically Safe (ATEX) version available
- Multitone Mk7, Mk6 and POCSAG code formats
- Fully compatible with all Multitone paging systems

For more information on our products please call:

+44 (0)1506 418198

or visit:

www.multitone.com

Designed for tough environments

The RPR750 is supplied in a tough, dustproof and water-resistant case, protected to IP54. The specially designed grip-tight clip enables you to carry your pager in your pocket, bag or belt, keeping your hands free. Intrinsically Safe (ATEX) versions are also available, allowing the RPR750 to operate in most hazardous and hostile environments.

Advanced messaging features

With simple button operation and plain language prompts, the RPR750 ensures ease of use whatever the conditions. Supporting up to 120-character messages, a 600-character message memory, and multiple language support, the RPR750 is extremely easy to use.

Multiple alert options

With eight 'system generated' tone alerts, the type of paging call is instantly recognisable, whether it is a crash call, code blue, fire alarm or security alert - instant response is assured. In addition, the following selectable alert functions are included:

- vibrate alert
- optional warble alert – provides enhanced alert definition
- escalating alert – elicits urgent response
- extended message alert – reminds the user of unread messages
- silent alert - flashing lamp and vibrate modes for zero disturbance

The RPR750 delivers consistent, mission critical day-to-day performance. With its ability to deliver text, voice and stored speech, the RPR750 ensures robust and resilient messaging whatever the environment.



Technical specification

RPR751 (HF) radio performance

- Frequency range: 25-54MHz
- Channel spacing: 12.5/20/25kHz

RPR752 (VHF) radio performance

- Frequency range: 137-174MHz
- Channel spacing: 12.5/20/25kHz

RPR753 (UHF) radio performance

- Frequency range: 407-417MHz and 430-470MHz
- Channel spacing: 12.5/20/25kHz

Battery - standard version

- Single AA alkaline (LR6)
- AA NiMH (rechargeable)

Battery - Intrinsically Safe version

- Single AAA alkaline (disposable)
- AAA NiMH (rechargeable)

Code format

- Multitone Mk7, Mk6 and POCSAG CCIR no.1
- Note: speech features are not available on POCSAG variants

Physical characteristics

- Size: 81mm (h) x 57mm (w) x 21mm (d)
- Weight: 60g
- Weight including battery: 83g

Multitone Electronics plc, Geddes House, Kirkton North, Livingston, West Lothian, EH54 6GU
Tel: +44 (0)1506 418198 Fax: +44 (0)1506 411711 Email: info@multitone.com Web: www.multitone.com

This brochure is for guidance only. Products and services offered are subject to availability and may differ from those described or illustrated in this brochure as a result of changes. Specifications are subject to change without notice. Multitone Electronics plc is part of Kantone Holdings Ltd, a member of the Champion Technology group of companies. Registered office: Multitone Electronics plc, Shortwood Copse Lane, Kempshott, Basingstoke, Hampshire, RG23 7NL. Registered in England No. 256314.

Literature No: NPL010 Issue: 03



FM 20122